

SW80010-D

8 Port 10/100Mbps Ethernet Switch



SPECIFICATION

Standards and Protocols	IEEE802.3, 802.3u, 802.3x, CSMA/CD, TCP/IP
Basic Function	Wire-speed Performance MAC Address Auto-Learning and Auto-aging IEEE802.3x flow control for Full-Duplex Mode and backpressure for Half-Duplex Mode
MAC Address Table	1k
Forwarding Rate	10BASE-T: 14880pps/port 100BASE-TX: 148800pps/port
Transmission Method	Store-and-Forward
Ports	8 10/100Mbps Auto-Negotiation RJ45 ports (Auto MDI/MDIX)
Network Media	10Base-T: UTP category 3, 4, 5 cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m) 100Base-Tx: UTP category 5, 5e cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m)
LED Indicators	Power, Link/Act (1, 2, 3, 4, 5)
Environment	Operating Temperature: 0 C~40 C (32°F~104°F) Storage Temperature : -40°C~70°C (-40°F~158°F) Relative Humidity :10% ~ 90%, non condensation Storage Humidity : 5%~95% non-condensing
Power	External Power Adapter

FEATURE

- Built-in 8 Port Fast Ethernet
- Supports 200Mbps in Full Duplex Mode
- Ideal for Fast Home Networks, Gaming and Video
- Ideal for SME Businesses looking higher port densities
- Stylish and compact design with low Power Consumption
- Plug n' Play for all Computers, Servers, Routers, Media Centres, Game Consoles and more



Energy
Efficient
Ethernet



© 2011 Dynamode
Details correct at going to press. E&OE
All Trademarks Acknowledged