

RoHS Compliant



US-701

USB 4xRS232 1Mbaud

"SERIAL CARDS ENGINEERED TO EXCEED EXPECTATIONS"



Description

USB to Serial providing four RS232 serial ports. Up to 921,600 data transfer rates and the 128 byte transmit and 384 byte receive FIFOs, coupled with 1Mbit line drivers deliver uncompromising performance on your laptop/PC.

USB to serial is the quick low cost way to connect your computer to a serial comms enabled device. Boost software gives industry leading functionality and compatibility.

These products do away with traditional issues with USB technology so you can buy with confidence!

With Brainboxes industry renowned Lifetime Warranty and Lifetime Support!

Features

- 4 port RS232
- USB
- 128 Byte Tx and 384 Byte Rx FIFOs
- Up to 921,600 Baud
- 4xDB9 connector (9 Pin Male)
- Drivers for all popular operating systems
- Sample Programs, Test & Terminal software
- Lifetime Support
- Lifetime Warranty (registration required)
- Supplied with USB cable
- Supplied with rubber feet for office environment

Accessories



MK-059:
Wall Mounting Kit for
4&8 Port ES/US

MK-070:
Snap-in DIN Clip Kit for
4&8 Port ES/US



Software

Microsoft signed drivers (easy installation & robust operation) for:

- Windows 7 32 bit and 64 bit editions
- Windows Vista 32 bit and 64 bit editions
- Windows XP 32 bit & 64 bit editions



As well as: full product documentation, a thorough troubleshooting guide and terminal software. Detailed sample source code for many popular programming languages. Further OS support on next page.



ORDER






Description
USB 4xRS232 1Mbaud

Code
US-701



USB 4xRS232 1Mbaud

US-701: Full Specification

Port 	Ports Connector FIFO size Operating Distance Cable	4 x RS232 4xDB9 connector (9 Pin Male) USB Type B High Retention 384 RX FIFO + 128 TX FIFO EIA - RS232 Standard USB Cable
Port Settings 	Baud Rate Data Bits Parity Stop Bits Flow Control Tx/Rx Modes	921,600 7 or 8 Odd, Even, None, Mark or Space 1 or 2 RTS/CTS, DTR/DSR, XON/XOFF Point to Point
Interface	OS Compatibility BUS	Windows 7 32 bit & 64 bit Editions Windows Vista 32 bit & 64 bit Editions Windows XP 32 bit & 64 bit Editions USB :
Approvals 	Other Approvals Microsoft Approvals	WEEE RoHS EMC: CE Microsoft Certified Gold Partner Microsoft Certified Gold Partner Windows 7 32 bit & 64 bit editions Windows Vista 32 bit & 64 bit editions Windows XP 32 bit & 64 bit editions
General	PCB Layers Power Consumption Weight Size	4 300mA @ 5V 1.020 Kg 135 x 215 x 35 mm
Box Content	Packaging Device	Installation CD (including manual, Microsoft signed drivers & utilities) USB 4xRS232 1Mbaud
Product Support 	Warranty Support	Lifetime (online registration required) Lifetime Web, Email and Phone Support from fully qualified, friendly staff who work in and alongside the Product Development Team
Additional 	OEM option Made In Customisable	Available for bulk buy OEM Manufactured in the UK by Brainboxes Winner 2005 European Electronics Industry Awards "Manufacturer of the Year" Brainboxes operate a "Perfect Fit Custom Design" policy for volume users. More Info: sales@brainboxes.com