









Get ahead with the curved GCB3486WQSCP-B1 Gold Phoenix featuring 240Hz refresh rate, 0.4ms response time and KVM Switch

Dive into an immersive gaming experience with the 34" GCB3486WQSCP-B1 curved gaming monitor. Designed with a 1500R curvature, it wraps around your field of view for a more engaging and comfortable experience. The VA panel with an ultra-wide 3440x1440 resolution delivers deep contrasts and vibrant colours, making every detail stand out.

With an ultra-fast 240Hz refresh rate, motion is incredibly smooth and fluid, ensuring top-tier performance for competitive gaming. The rapid 0.4ms response time (MPRT) minimises motion blur, keeping your gameplay crisp and precise. HDR400 enhances brightness and contrast for more lifelike visuals, while FreeSync Premium reduces screen tearing and stuttering for a seamless experience.

Seamlessly switch between work and play with the built-in KVM function, allowing you to control multiple devices with a single set of peripherals. Additionally, the monitor features both Picture-in-Picture (PiP) and Picture-by-Picture (PbP) functions, enabling efficient multitasking and boosting productivity.



CURVED DESIGN 1500R

The 1500R curvature of the screen guarantees a realistic and comfortable viewing experience allowing you to really immerse yourself in the game.



240Hz & 0.4ms MPRT

With 240Hz refresh rate and 0.4ms MPRT response time the force is with you! Make split second decisions and be sure the image on the screen is always sharp and smooth.

01 DISPLAY CHARACTERISTICS

Diagonal 34", 86.4cm Panel VA Curved 1500R Native resolution 3440 x 1440 @240Hz (4.9 megapixel UWQHD, DisplayPort) Aspect ratio 21:9 Panel brightness 500 cd/m² Static contrast 4000:1 Advanced contrast 80M:1 Response time (MPRT) 0.4ms Viewing zone horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89° Colour support 16.7mln 8bit (sRGB: 99%; NTSC: 72%) Horizontal Sync 24 - 360kHz Viewable area W x H 797 x 334mm, 31.4 x 13.1"	Design	curved
Curved 1500R Native resolution 3440 x 1440 @240Hz (4.9 megapixel UWQHD, DisplayPort) Aspect ratio 21:9 Panel brightness 500 cd/m² Static contrast 4000:1 Advanced contrast 80M:1 Response time (MPRT) 0.4ms Viewing zone horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89° Colour support 16.7mln 8bit (sRGB: 99%; NTSC: 72%) Horizontal Sync 24 - 360kHz	Diagonal	34", 86.4cm
Native resolution3440 x 1440 @240Hz (4.9 megapixel UWQHD, DisplayPort)Aspect ratio21:9Panel brightness500 cd/m²Static contrast4000:1Advanced contrast80M:1Response time (MPRT)0.4msViewing zonehorizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°Colour support16.7mln 8bit (sRGB: 99%; NTSC: 72%)Horizontal Sync24 - 360kHz	Panel	VA
Aspect ratio 21:9 Panel brightness 500 cd/m² Static contrast 4000:1 Advanced contrast 80M:1 Response time (MPRT) 0.4ms Viewing zone horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89° Colour support 16.7mln 8bit (sRGB: 99%; NTSC: 72%) Horizontal Sync 24 - 360kHz	Curved	1500R
Panel brightness500 cd/m²Static contrast4000:1Advanced contrast80M:1Response time (MPRT)0.4msViewing zonehorizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°Colour support16.7mln 8bit (sRGB: 99%; NTSC: 72%)Horizontal Sync24 - 360kHz	Native resolution	3440 x 1440 @240Hz (4.9 megapixel UWQHD, DisplayPort)
Static contrast Advanced contrast 80M:1 Response time (MPRT) 0.4ms Viewing zone horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89° Colour support 16.7mln 8bit (sRGB: 99%; NTSC: 72%) Horizontal Sync 24 - 360kHz	Aspect ratio	21:9
Advanced contrast 80M:1 Response time (MPRT) 0.4ms Viewing zone horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89° Colour support 16.7mln 8bit (sRGB: 99%; NTSC: 72%) Horizontal Sync 24 - 360kHz	Panel brightness	500 cd/m ²
Response time (MPRT) 0.4ms Viewing zone horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89° Colour support 16.7mln 8bit (sRGB: 99%; NTSC: 72%) Horizontal Sync 24 - 360kHz	Static contrast	4000:1
Viewing zonehorizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°Colour support16.7mln 8bit (sRGB: 99%; NTSC: 72%)Horizontal Sync24 - 360kHz	Advanced contrast	80M:1
Colour support16.7mln 8bit (sRGB: 99%; NTSC: 72%)Horizontal Sync24 - 360kHz	Response time (MPRT)	0.4ms
Horizontal Sync 24 - 360kHz	Viewing zone	horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
	Colour support	16.7mln 8bit (sRGB: 99%; NTSC: 72%)
Viewable area W x H 797 x 334mm, 31.4 x 13.1"	Horizontal Sync	24 - 360kHz
	Viewable area W x H	797 x 334mm, 31.4 x 13.1"
Pixel pitch 0.232mm	Pixel pitch	0.232mm
Colour black	Colour	black

02 INTERFACES / CONNECTORS / CONTROLS

Signal input	HDMI x2 (v.2.1 3440x1440 @240Hz) DisplayPort x1 (v.1.4, 3440 x 1440@ 240Hz)
USB HUB	x3 (2x Type A v.3.2 Gen 1 (5Gbps, 4.5W) 1x Type C (5Gbps, 10W))
USB-C DOCK	x1 (Power delivery 95W, LAN, USB v.3.2 (Gen 1, 5Gbit))
HDCP	yes
Headphone connector	yes
RJ45 (LAN)	x1

03 FEATURES

KVM switch	yes
Blue light reducer	yes
Flicker free	yes
Adaptive Sync support	FreeSync Premium - HDMI: 3440 x 1440 @48-240Hz, DP / USB-C: 3440 x 1440 @48-240Hz, VRR / ALLM
HDR	HDR400
OSD languages	EN, DE, FR, ES, IT, RU, JP, CZ, NL, PL
Control buttons	Power Indicator, Joystick: Power / Menu (Center), Up / Signal Select, Down, Left / i-Style Colour / Night Mode / Blue Light Reducer, Right / Volume
User controls	picture adjust (contrast, brightness, OD, HDR, AMD FreeSync Premium, ACR, night mode, blue light reducer, motion blur reduction, gamma), input select, audio settings (volume, mute), store user settings (user modes), colour settings (6-axis, colour temperature, user preset, black tuner), image adjust (i-Style Colour, x-res technology, sharpness, HDMI range, direct drive mode, video mode adjust), language, setup menu (OSD horizontal position, OSD vertical position, OSD time, opening logo, power LED, USB-C speed, DDC/CI control, USB charge, PIP/PBP, KVM, DSC compression), display information, reset
Speakers	2 x 5W
Convenience	Kensington-lock™ prepared, DDC2B, Mac OSX

Display position adjustments	height, tilt
Height adjustment	130mm
Tilt angle	18.5° up; 3.5° down
VESA mounting	100 x 100mm
Cable management system	yes



ACCESSORIES INCLUDED

Cables	power (1.85m), USB (1.5m), HDMI (1.85m), DP (1.85m)
Other	quick start guide, safety guide



POWER MANAGEMENT

Power supply unit	internal
Power supply	AC AC - 100V, 240/V, 50Hz
Power usage	52W typical, 0.5W stand by, 0.3W off mode



SUSTAINABILITY

Regulations	CE, TÜV-GS, EAC, VCCI-B, PSE, RoHS support, ErP, WEEE, REACH, UKCA
Energy efficiency class (Regulation (EU) 2017/1369)	F
EPEAT	EPEAT is a comprehensive environmental rating that helps identify greener computers and other electronic equipment. The Bronze certification means the monitor meets all required criteria. EPEAT Bronze is valid in countries where iiyama registers the product. Please visit www.epeat.net for the registration status in your country.
REACH SVHC	above 0.1%: Lead



DIMENSIONS / WEIGHT

Product dimensions W x H x D	808 x 414.5 (544.5) x 275mm
Box dimensions W x H x D	982 x 490 x 190mm
Weight (without box)	8kg
EAN code	4948570125173

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.

© IIYAMA CORPORATION. ALL RIGHTS RESERVED